NSN 5305-01-520-3840

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-520-3840

| Thread Class: |
|---|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.469 inches |
| Fastener Length: |
| Between 1.390 inches and 1.437 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.464 inches and 0.506 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Point Length: |
| 0.060 inches |
| Point Style: |
| Flat |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.2500 inches |
| Grip Length: |
| Between 0.927 inches and 0.947 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 6400 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel |
| Material Specification: |
| Nas98 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas672 federal standard single treatment response |
| Thread Series Designator: |
| Unjf |
| |

NSN 5305-01-520-3840

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

