NSN 5305-01-520-6706

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-520-6706

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| |
| Right-hand |
| Thread Length: Between 0.476 inches and 0.526 inches |
| |
| Fastener Length: |
| Between 1.297 inches and 1.327 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.429 inches and 0.479 inches |
| Grip Diameter: |
| Between 0.311 inches and 0.312 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| End Application: |
| F-16 acft |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.914 inches and 0.944 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| 91.0 degrees |
| Product Name: |
| Screw-low hd, skirt hd |
| Material: |
| Cadmium |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas672 assn standard all treatment responses |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-520-6706

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

