NSN 5305-01-520-8702

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-520-8702

| View Online at https://aerobasegroup.com/nsn/5305-01-520-8702 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.250 inches |
| Fastener Length: |
| 0.250 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.110 inches and 0.156 inches |
| Locking Feature: |
| Slotted |
| Internal Drive Style: |
| Cross recess type iii |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Screw Material: |
| Iron alloy 660 |
| Locking Feature Material: |
| Plastic polyamide |
| Screw Material Specification: |
| Ams5737 assn standard single material response |
| Locking Feature Material Specification: |
| Mil-dtl-18240, type p military specification single material response |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

NSN 5305-01-520-8702

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-dtl-18240 spec.

