## NSN 5305-01-520-9371

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-520-9371

view Offilite at https://aerobasegroup.com/hist//3505-01-525-5571
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.260 inches
Fastener Length:
0.465 inches
Head Style:
Undercut pan no. 2
Head Diameter:
0.547 inches
Head Height:
0.127 inches
Spline Major Diameter:
0.155 inches
Grip Diameter:
0.189 inches
Internal Drive Style:
Torx
End Application:
Mv-22 (v-22 Irip 1 e-nsn isil
Thread Diameter:
0.190 inches
Grip Length:
0.062 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
3180 pounds per square inch
Criticality Code Justification:
Agav
Product Name:
Screw, shear, pan head, close tolerance, short thread, six lobe recess, 95 ksi fsu
Material:
Iron alloy 660
Material Specification:
Ams 5731 federal specification 1st material response or ams5732 federal specification 2nd material response or ams5737 federal
specification 3rd material response or ams5853 federal specification 4th material response
Surface Treatment:

Passivate

**Surface Treatment Specification:** 

Ams qq-p-35 federal specification single treatment response

## NSN 5305-01-520-9371

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0