NSN 5305-01-520-9371

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-520-9371

| view Offilite at https://aerobasegroup.com/hist//3505-01-525-5571 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.260 inches |
| Fastener Length: |
| 0.465 inches |
| Head Style: |
| Undercut pan no. 2 |
| Head Diameter: |
| 0.547 inches |
| Head Height: |
| 0.127 inches |
| Spline Major Diameter: |
| 0.155 inches |
| Grip Diameter: |
| 0.189 inches |
| Internal Drive Style: |
| Torx |
| End Application: |
| Mv-22 (v-22 Irip 1 e-nsn isil |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 0.062 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 3180 pounds per square inch |
| Criticality Code Justification: |
| Agav |
| Product Name: |
| Screw, shear, pan head, close tolerance, short thread, six lobe recess, 95 ksi fsu |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 federal specification 1st material response or ams5732 federal specification 2nd material response or ams5737 federal |
| specification 3rd material response or ams5853 federal specification 4th material response |
| Surface Treatment: |

Passivate

Surface Treatment Specification:

Ams qq-p-35 federal specification single treatment response

NSN 5305-01-520-9371

Close Tolerance Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0