## NSN 5305-01-520-9372

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-520-9372

| View Online at https://aerobasegroup.com/nsn/5305-01-520-9372  |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.260 inches   |
| Fastener Length:   |
| 0.465 inches   |
| Head Style:  |
| Undercut pan no. 2   |
| Head Diameter:   |
| 0.547 inches   |
| Head Height:   |
| 0.127 inches   |
| Spline Major Diameter:   |
| 0.155 inches   |
| Grip Diameter:   |
| 0.189 inches   |
| Internal Drive Style:  |
| Torx   |
| End Application:   |
| Mv-22 (v-22 Irip 1 e-nsn isil  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| 0.062 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 3180 pounds per square inch  |
| Product Name:  |
| Screw, shear, pan head, close tolerance, short thread, six lobe recess, 95 ksi fsu   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5731 federal specification 1st material response or ams 5732 federal specification 2nd material response or ams 5737 federal |
| specification 3rd material response or ams 5853 federal specification 4th material response                                      |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Ams-qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |

Unjf

## NSN 5305-01-520-9372

Close Tolerance Screw - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0