

View Online at <https://aerobasegroup.com/nsn/5305-01-520-9376>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.260 inches

Fastener Length:

1.341 inches

Head Style:

Undercut pan no. 2

Head Diameter:

0.547 inches

Head Height:

0.127 inches

Spline Major Diameter:

0.155 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Internal Drive Style:

Torx

End Application:

Mv-22 (e-nsn isil)

Thread Diameter:

0.190 inches

Grip Length:

0.938 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

3180 pounds per square inch

Product Name:

Screw, shear, pan head, close tolerance, short thread, six lobe recess, 95 ksi fsu

Material:

Iron alloy 660

Material Specification:

Ams 5731 federal specification 1st material response or ams 5732 federal specification 2nd material response or ams 5737 federal specification 3rd material response or ams 5853 federal specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0