

View Online at <https://aerobasegroup.com/nsn/5305-01-521-2025>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

0.901 inches

Head Style:

Flat fillister

Head Diameter:

Between 0.306 inches and 0.313 inches

Head Height:

Between 0.103 inches and 0.118 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1123 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.