# NSN 5305-01-521-2025

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-521-2025

Thread Class:

3a

**Thread Direction:** 

Right-hand

# Thread Length:

0.276 inches

## Fastener Length:

0.901 inches

#### Head Style:

Flat fillister

Head Diameter:

Between 0.306 inches and 0.313 inches

## Head Height:

Between 0.103 inches and 0.118 inches

#### Grip Diameter:

Between 0.188 inches and 0.189 inches

#### **Internal Drive Style:**

Offset cruciform (torque set)

### Thread Diameter:

0.190 inches

## Grip Length:

0.625 inches

### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

### Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

### Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

### Thread Series Designator:

Unjf

### **Specification Data:**

80205-nas1123 professional/industrial association standard

### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5305-01-521-2025

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.