NSN 5305-01-521-8876

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-521-8876

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.381 inches and 0.431 inches
Fastener Length:
Between 0.579 inches and 0.609 inches
Head Style:
Fillister countersunk
Head Diameter:
Between 0.2966 inches and 0.3016 inches
Head Height:
0.013 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole and 0.075 inches first hole
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.478 inches first hole
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5305-01-521-8876

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0