
NSN 5305-01-521-8876

Close Tolerance Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.381 inches and 0.431 inches Fastener Length: Between 0.579 inches and 0.609 inches **Head Style:** Fillister countersunk **Head Diameter:** Between 0.2966 inches and 0.3016 inches **Head Height:** 0.013 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches Shank Unthreaded Hole Diameter: 0.070 inches first hole and 0.075 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Grip Length: Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.478 inches first hole Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-01-521-8876

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

