
3a

Socket Head Cap Screw - Page 1 of 2





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.622 inches and 0.625 inches Fastener Length: Between 0.622 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches Hole Diameter: Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hole Configuration Style: Round internal hexagon **Special Features:** Modified from ms24673-10 Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 military specification single treatment response

Thread Series Designator:

Unf

3

28

NSN 5305-01-521-9903

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.

