

View Online at <https://aerobasegroup.com/nsn/5305-01-521-9974>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.497 inches and 0.500 inches

**Fastener Length:**

Between 0.497 inches and 0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Hole Diameter:**

Between 0.044 inches and 0.050 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Round internal hexagon

**Special Features:**

Modified from ms2473-2

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or aluminum or steel comp 316 or steel comp 384

**Material Specification:**

Astm a493 assn standard all material responses

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c-83488 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.