
Socket Head Cap Screw - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.960 inches and 1.000 inches

#### Fastener Length:

Between 0.960 inches and 1.000 inches

#### **Head Style:**

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

#### Head Height:

Between 0.244 inches and 0.250 inches

### Internal Drive Style:

Hexagon

### Thread Diameter:

0.250 inches

### Width Across Flats:

Between 0.1875 inches and 0.1900 inches

### Thready Qty Per Inch (tpi):

20

### **Special Features:**

Modified from ms16995-54

Material:

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

### **Material Specification:**

Astm f593 assn standard all material responses

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

Mil-c-83488 military specification single treatment response

# **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-522-1309

Socket Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-83488 spec.

