## NSN 5305-01-522-1698



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-522-1698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.210 inches and 1.250 inches **Fastener Length:** Between 1.710 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.313 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.2500 inches and 0.2530 inches Thready Qty Per Inch (tpi): 16 **Special Features:** Modified from ms16995-84 Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** Astm f593 assn standard all material responses **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig: A003b0

## NSN 5305-01-522-1698

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.