## NSN 5305-01-522-4298

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-522-4298

Thread Cla	SS:
2a	
Thread Dire	ection:
Right-hand	
Thread Ler	ngth:
0.750 inche	S
Fastener L	ength:
Between 0.	719 inches and 0.750 inches
Head Style	:
Pan	
Head Diam	eter:
Between 0.4	473 inches and 0.492 inches
Head Heigl	nt:
Between 0.	162 inches and 0.175 inches
Internal Dri	ive Style:
Cross reces	ss type 1
Thread Dia	meter:
0.250 inche	S
Thready Q	y Per Inch (tpi):
28	
Min. Tensil	e Strength (psi):
80000 pour	nds per square inch
Screw Mate	erial:
Steel comp	304 or steel comp 316
Screw Mate	erial Specification:
Qq-s-763 fe	deral specification single material response and fed.Std.66 federal standard single material response
Screw Surf	ace Treatment:
Aluminum	
Special Fea	atures:
Altered from	n ms51958-81 by addition of a high purity aluminum coating and a fluoropolymer surface treatment
Thread Ser	ies Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A500d0	