NSN 5305-01-522-7550

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-522-7550



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.863 inches and 0.894 inches **Fastener Length:** Between 0.863 inches and 0.894 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.442 inches and 0.507 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **End Application:** Ch-53g helicopter **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Screw, self-locking, flat 100 degree head, full thread Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1189 professional/industrial association standard

NSN 5305-01-522-7550

Socket Head Cap Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0