## NSN 5305-01-522-9516

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-522-9516 **Thread Class:** За Fastener Length: 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.347 inches **Head Height:** Between 0.105 inches and 0.115 inches **Washer Quantity:** 2 **Internal Drive Style:** Cross recess type 1 **End Application:** Console **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.293 inches **Secondary Washer Outside Diameter:** Between 0.302 inches and 0.322 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches **Secondary Washer Material Thickness:** Between 0.025 inches and 0.035 inches Color: Black Material: Stainless steel **Surface Treatment:** Oxide **Thread Series Designator:** Unc

## NSN 5305-01-522-9516

Assembled Washer Screw - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0