Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-522-9525

| Three | |
|----------|---|
| | d Class: |
| 3a | |
| | d Direction: |
| Right-h | |
| | ner Length: |
| 0.625 i | |
| Head S | Style: |
| Pan | |
| | Diameter: |
| | en 0.306 inches and 0.347 inches |
| | Height: |
| | en 0.105 inches and 0.115 inches |
| Washe | er Quantity: |
| 2 | |
| | al Drive Style: |
| | recess type 1 |
| End A | pplication: |
| Conso | le |
| Thread | d Diameter: |
| 0.164 i | inches |
| Thread | dy Qty Per Inch (tpi): |
| 32 | |
| Secon | dary Washer Relationship To Primary Washer: |
| Not ide | entical |
| Secon | dary Washer Style: |
| Flat | |
| Prima | ry Washer Outside Diameter: |
| 0.293 i | inches |
| Secon | dary Washer Outside Diameter: |
| Betwee | en 0.302 inches and 0.322 inches |
| Prima | ry Washer Style: |
| Split he | elical ring |
| Prima | ry Washer Material Thickness: |
| 0.040 i | inches |
| Secon | dary Washer Material Thickness: |
| Betwee | en 0.025 inches and 0.035 inches |
| Color: | |
| Black | |
| Materi | al: |
| Stainle | ess steel |
| Surfac | e Treatment: |
| Oxide | |
| | |

NSN 5305-01-522-9525

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0