NSN 5305-01-523-4928

Thread Class:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-523-4928

Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.158 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 42.0 rockwell c
Minimum Yield Strength:
120000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response

NSN 5305-01-523-4928

Socket Head Cap Screw - Page 2 of 2



Precious Material And Location:
silver
Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2411 assn standard single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A003b0