NSN 5305-01-523-9859



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-523-9859 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.2965 inches and 0.3435 inches **Fastener Length:** Between 0.2965 inches and 0.3435 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.314 inches **Hole Diameter:** Between 0.046 inches and 0.056 inches **Internal Drive Style:** Cross recess type iii **End Application:** F-15 acft **Thread Diameter:** 0.1900 inches **Hole Quantity:** Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):

160000 pounds per square inch

Criticality Code Justification:

Aasb

Product Name:

Screw, hex head

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Head Hole Configuration Style:

Hexagon corners

NSN 5305-01-523-9859

Machine Screw - Page 2 of 2

Fiig: A500d0



Bearing Surface Of Head Surface Finish:
63.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No