## NSN 5305-01-524-1501

Close Tolerance Screw - Page 1 of 2



Thread Class:         3a         Thread Direction:         Right-hand         Thread Length:         0.430 inches         Fastener Length:         0.393 inches         Head Style:         Round extended washer         Head Diameter:         0.375 inches         Head Height:         0.094 inches         Extended Washer Diameter:         0.437 inches         Extended Washer Diameter:         0.437 inches         Cozy inches         Grip Diameter:         0.437 inches         Cozy inches         Charlow Extended Washer Thickness:         0.437 inches         Diameter:         0.437 inches         Charlo Diameter:         0.437 inches         Charlow Extended Washer Thickness:         0.437 inches         Internal Drive Style:         Charlow Extended Clare Thickness:         0.439 inches         Interd Diameter:         0.439 inches         Interd Diameter:         0.439 inches         Charlow Extended Clare Thickness         0.439 inches         Diameter
Tread Direction:         Right-hand         Thread Length:         0.430 inches         Fastener Length:         0.938 inches         Head Style:         Round extended washer         Head Diameter:         0.375 inches         Head Height:         0.094 inches         Extended Washer Diameter:         0.437 inches         Extended Washer Thickness:         0.027 inches         Grip Diameter:         0.027 inches         Internal Drive Style:         Cruciform ribbed         End Application:         Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)         Thread Diameter:         0.190 inches         Grip Length:         0.375 inches         End Application:         0.190 inches         Grip Length:         0.375 inches         Grip Length:         0.375 inches         Thread Quy Per Inch (pi):         32         Min. Tensile Strength (psi):         2000 pounds per square inch
Right-hand         Thread Length:         0.430 inches         Fastener Length:         0.338 inches         Head Style:         Round extended washer         Head Diameter:         0.375 inches         Head Height:         0.094 inches         Extended Washer Diameter:         0.437 inches         Extended Washer Thickness:         0.437 inches         6.439 inches         Chrip Diameter:         0.437 inches         0.437 inches         Chrip Diameter:         0.438 inches         Chrip Diameter:         0.439 inches         Diameter:         0.439 inches         Extended Washer Thickness:         0.437 inches         Chrip Liameter:         0.438 inches         Extended Chrip Lington:         1.490 inches         Chrip Lington:         1.490 inches         Grip Length:         0.375 inches         Thready Qty Per Inch (tpi):         32         Min Tensile Strength (psi):         2000 pounds per square inch
Tread Length:         0.430 inches         Fastener Length:         0.938 inches         Head Style:         Round extended washer         Head Diameter:         0.375 inches         Head Height:         0.094 inches         Extended Washer Diameter:         0.437 inches         Extended Washer Diameter:         0.437 inches         Extended Washer Thickness:         0.027 inches         Grip Diameter:         0.438 inches         Internal Drive Style:         Cruciform ribbed         End Application:         0.190 inches         Strip Length:         0.190 inches         Grip Length:         0.190 inches         Ended Diameter:         0.190 inches         Internal Drive Style:         Cruciform ribbed         Endergettion:         0.190 inches         Grip Length:         0.375 inches         Thready Qty Per Inch (tpi):         0.375 inches         Thready Diameter:         0.375 inches         Diameter:         0.375 inches         Diameter:
0.430 inches Fastener Length: 0.938 inches Head Style: Round extended washer Head Diameter: 0.375 inches Head Height: 0.094 inches Extended Washer Diameter: 0.094 inches Extended Washer Diameter: 0.037 inches Extended Washer Thickness: 0.027 inches Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thread Diameter: 0.375 inches Cruciform ribbed
Fastener Length:0.938 inchesHead Style:Round extended washerHead Diameter:0.375 inchesHead Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.027 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cruciform ribbedEnd Application:0.190 inchesEnd Application:0.190 inchesCruciform ribbedEnd Application:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.375 inchesThready Qup Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
0.938 inchesHead Style:Round extended washerHead Diameter:0.375 inchesHead Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.437 inchesExtended Washer Thickness:0.027 inchesGrip Diameter:0.189 inchesCuciform ribbedEnd Application:Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.190 inchesGrip Length:0.375 inchesThready Gy Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
Head Style:Round extended washerHead Diameter:0.375 inchesHead Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.427 inchesGrip Diameter:0.428 inchesColor inchesGrip Diameter:0.489 inchesDuttersOutgoin of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Langett0.190 inchesThread Diameter:0.190 inchesGrip Langett1.190 inchesGrip Langett0.190 inchesChready Oty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
Round extended washerHead Diameter:0.375 inchesHead Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.027 inchesGrip Diameter:0.189 inchesInternal Drive Style:Cruciform ribbedEnd Application:Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Length:0.375 inchesGrip Length:0.375 inchesThready Cty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
Head Diameter:0.375 inchesHead Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.027 inchesCo27 inchesO194 inches0.189 inchesCrip Diameter:0.189 inchesCruciform ribbedEnd Application:Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
0.375 inches  Head Height: 0.094 inches  Extended Washer Diameter: 0.437 inches  Extended Washer Thickness: 0.027 inches  Carip Diameter: 0.027 inches  Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Head Height:0.094 inchesExtended Washer Diameter:0.437 inchesExtended Washer Thickness:0.027 inchesGrip Diameter:0.129 inchesInternal Drive Style:Cruciform ribbedEnd Application:Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
0.094 inches Extended Washer Diameter: 0.437 inches Extended Washer Thickness: 0.027 inches Grip Diameter: 0.129 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Extended Washer Diameter: 0.437 inches Extended Washer Thickness: 0.027 inches Grip Diameter: 0.129 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
0.437 inches Extended Washer Thickness: 0.027 inches Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Extended Washer Thickness: 0.027 inches Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
0.027 inches Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Grip Diameter: 0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
0.189 inches Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Internal Drive Style: Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Cruciform ribbed End Application: Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
End Application:Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)Thread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil) Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Thread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):2000 pounds per square inch
0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch
Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         2000 pounds per square inch
32 <b>Min. Tensile Strength (psi):</b> 2000 pounds per square inch
Min. Tensile Strength (psi): 2000 pounds per square inch
2000 pounds per square inch
Criticality Code, Justification
Criticality Code Justification:
Agav
Product Name:
Screw, washer head, close tolerance, long thread, 95 ksi fsu
Material:
Steel comp 4340
Material Specification:
Ams6415 assn standard 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment:
Cadmium

## NSN 5305-01-524-1501

Close Tolerance Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.