## NSN 5305-01-524-1506

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-524-1506

Thread Class:		
3a		
Thread Direction:		
Right-hand		
Thread Length:		
0.398 inches		
Fastener Length:		
1.243 inches		
Head Style:		
Round extended washer		
Head Diameter:		
0.312 inches		
Head Height:		
0.087 inches		
Extended Washer Diameter:		
0.375 inches		
Extended Washer Thickness:		
0.025 inches		
Grip Diameter:		
0.163 inches		
Internal Drive Style:		
Cruciform ribbed		
End Application:		
Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)		
Thread Diameter:		
0.164 inches		
Grip Length:		
0.719 inches		
Thready Qty Per Inch (tpi):		
32		
Min. Tensile Strength (psi):		
1425 pounds per square inch		
Criticality Code Justification:		
Agav		
Product Name:		
Screw, washer head, close tolerance, long thread, 95 ksi fsu		
Material:		
Steel comp 4340		
Material Specification:		
Ams6415 assn standard 1st material response or mil-s-6049 military specification 2nd material response		
Surface Treatment:		

Cadmium

## NSN 5305-01-524-1506

Close Tolerance Screw - Page 2 of 2



Surface Treatment Specification:			
Qq-p-416,	type 2,	class2 federal specification single treatment response	

**Thread Series Designator:** 

Unjc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.