NSN 5305-01-524-1516

Cadmium

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-524-1516

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.430 inches
Fastener Length:
1.188 inches
Head Style:
Round extended washer
Head Diameter:
0.375 inches
Head Height:
0.094 inches
Extended Washer Diameter:
0.437 inches
Extended Washer Thickness:
0.027 inches
Grip Diameter:
0.189 inches
Internal Drive Style:
Cruciform ribbed
End Application:
Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)
Thread Diameter:
0.190 inches
Grip Length:
0.625 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
2000 pounds per square inch
Criticality Code Justification:
Agav
Product Name:
Screw, washer head, close tolerance, long thread, 95 ksi fsu
Material:
Steel comp 4340
Material Specification:
Ams6415 assn standard 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment:

NSN 5305-01-524-1516

Close Tolerance Screw - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Qq-p-416, type 2, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.