

View Online at <https://aerobasegroup.com/nsn/5305-01-524-1528>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.424 inches

Fastener Length:

1.257 inches

Head Style:

Round extended washer

Head Diameter:

0.437 inches

Head Height:

0.101 inches

Extended Washer Diameter:

0.500 inches

Extended Washer Thickness:

0.030 inches

Grip Diameter:

0.249 inches

Internal Drive Style:

Cruciform ribbed

End Application:

Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)

Thread Diameter:

0.250 inches

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

3700 pounds per square inch

Criticality Code Justification:

Agav

Product Name:

Screw, washer head, close tolerance, long thread, 95 ksi fsu

Material:

Steel comp 4340

Material Specification:

Ams6415 assn standard 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.