## NSN 5305-01-524-1529

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-524-1529

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.398 inches
Fastener Length:
0.618 inches
Head Style:
Round extended washer
Head Diameter:
0.312 inches
Head Height:
0.087 inches
Extended Washer Diameter:
0.375 inches
Extended Washer Thickness:
0.025 inches
Grip Diameter:
0.163 inches
Internal Drive Style:
Cruciform ribbed
End Application:
Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)
Thread Diameter:
0.164 inches
Grip Length:
0.094 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
1425 pounds per square inch
Criticality Code Justification:
Agav
Product Name:
Screw, washer head, close tolerance, long thread, 95 ksi fsu
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 assn standard 3rd material

Surface Treatment:

response or ams5853 assn standard 4th material response

Passivate

## NSN 5305-01-524-1529

Close Tolerance Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0