

View Online at <https://aerobasegroup.com/nsn/5305-01-524-1536>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.399 inches

**Fastener Length:**

0.681 inches

**Head Style:**

Round extended washer

**Head Diameter:**

0.312 inches

**Head Height:**

0.087 inches

**Extended Washer Diameter:**

0.375 inches

**Extended Washer Thickness:**

0.025 inches

**Grip Diameter:**

0.163 inches

**Internal Drive Style:**

Cruciform ribbed

**End Application:**

Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)

**Thread Diameter:**

0.164 inches

**Grip Length:**

0.156 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

1425 pounds per square inch

**Criticality Code Justification:**

Agav

**Product Name:**

Screw, washer head, close tolerance, long thread, 95 ksi fsu

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 federal specification 3rd material response or ams5853 assn standard 4th material response

**Surface Treatment Specification:**

Qq-p-416, type 2, class2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0