

View Online at <https://aerobasegroup.com/nsn/5305-01-524-1542>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.430 inches

**Fastener Length:**

1.188 inches

**Head Style:**

Round extended washer

**Head Diameter:**

0.375 inches

**Head Height:**

0.094 inches

**Extended Washer Diameter:**

0.437 inches

**Extended Washer Thickness:**

0.027 inches

**Grip Diameter:**

0.189 inches

**Internal Drive Style:**

Cruciform ribbed

**End Application:**

Support of pre-provisioning items for which navicp phil acts as poe (e-nsn isil)

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2000 pounds per square inch

**Criticality Code Justification:**

Agav

**Product Name:**

Screw, washer head, close tolerance, long thread, 95 ksi fsu

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 assn standard 3rd material response or ams5853 assn standard 4th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0