NSN 5305-01-524-3134

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-524-3134 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 0.615 inches and 0.635 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.188 inches and 0.208 inches **Head Height:** Between 0.360 inches and 0.390 inches **First Diameter From Head:** 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Internal Drive Style:** Slot **End Application:** Nan/tpn-30a **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm-a581, 582-95b, (non-magnetic) 303 series. Condition a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm-a-380-96 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-524-3134

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0