NSN 5305-01-524-6001



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-524-6001 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** 0.720 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.295 inches and 0.334 inches **Grip Diameter:** Between 0.162 inches and 0.163 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams 6415 assn standard 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:**

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-524-6001

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.