NSN 5305-01-525-3903

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-525-3903

Thread Class:

Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.5175 inches and 0.5475 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.265 inches and 0.272 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torx **End Application:** F/a18 e/f aircraft **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.1775 inches and 0.1975 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Special Features:** Finish also treated with cetyl alcohol per mil-l-87132, ty i, grade b Material: Nickel alloy 718 **Material Specification:** Ams 5662, inconel 718 assn standard single material response **Surface Treatment:**

Aluminum

Surface Treatment Specification:

Mil-c-83488, ty ii, cls 3 military specification single treatment response

NSN 5305-01-525-3903

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-83488 spec.