## NSN 5305-01-525-4942



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-525-4942 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** 0.784 inches **Head Style:** Flat countersunk undercut **Head Diameter:** 0.226 inches **Head Height:** 0.039 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams-s-5000 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6322 assn standard 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** 

Unjc

### **Specification Data:**

80205-nas8602 professional/industrial association standard

### Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5305-01-525-4942

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0