NSN 5305-01-525-5100

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-525-5100

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.690 inches and 2.135 inches
Fastener Length:
Between 2.440 inches and 2.500 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
0.250 inches
Internal Drive Style:
Hexagon
End Application:
Hh60 helicopter
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Product Name:
Bolt modified
Special Features:
Altered item dwg, head changed to 0.250, made from nsn 5305-00-983-8075, pn ms16998-101.
Material:
Stainless steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf

NSN 5305-01-525-5100

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0