## NSN 5305-01-525-6995

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-525-6995 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.735 inches and 0.765 inches **Fastener Length:** Between 1.384 inches and 1.424 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Ams 648 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-525-6995

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0