NSN 5305-01-525-8941

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-525-8941 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.122 inches and 0.135 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 304 or steel comp 316 **Screw Material Specification:** Qq-s-763 federal specification single material response and fed.Std.66 federal standard single material response **Screw Surface Treatment:** Aluminum **Screw Surface Treatment Specification:** Mil-c-83488 military specification single treatment response **Special Features:** Altered from ms51958-66 by addition of high purity aluminum coating and a fluoropolymer surfact treatment. **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A500d0

NSN 5305-01-525-8941

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.