## NSN 5305-01-526-4032

За

**Thread Direction:** 

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-526-4032

Thread Class:

Right-hand
Thread Length:
Between 0.464 inches and 0.474 inches
Fastener Length:
Between 1.642 inches and 1.672 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.623 inches and 0.633 inches
Spline Major Diameter:
Between 0.154 inches and 0.156 inches
Grip Diameter:
0.311 inches
Point Diameter:
0.469 inches
Point Style:
Flat
Internal Drive Style:
Torx
Thread Diameter:
0.312 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degree tension head, gear drive recess
Special Features:
125 ksi shear strength
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf

## NSN 5305-01-526-4032

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0