NSN 5305-01-526-4053

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-526-4053 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 1.157 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** 0.249 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees **Product Name:** Screw-close tolerance, 100 degree countersunk, dovetail slot, sealant injection **Special Features:** Tapped hole in head, 0.138-32, unjc-3b threads. Distance from top of head to injection port is 0.510 inches. Injection port is 0.120l x 0.060w. Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-526-4053

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0