

View Online at <https://aerobasegroup.com/nsn/5305-01-526-4643>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.689 inches and 0.699 inches

**Fastener Length:**

Between 1.804 inches and 1.834 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.874 inches and 0.888 inches

**Spline Major Diameter:**

Between 0.154 inches and 0.156 inches

**Grip Diameter:**

0.436 inches

**Point Diameter:**

0.694 inches

**Point Style:**

Flat

**Internal Drive Style:**

Torx

**End Application:**

Fighter aircraft first f18 e/f

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Bolt, 100 degree tension head, gear drive recess

**Special Features:**

125 ksi shear strength

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0