NSN 5305-01-526-4680

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-526-4680

Between 0.689 inches and 0.699 inches
Fastener Length:
Between 1.491 inches and 1.521 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.874 inches and 0.888 inches
Spline Major Diameter:
Between 0.154 inches and 0.156 inches
Grip Diameter:
0.436 inches
Point Diameter:
0.694 inches
Point Style:
Flat
Internal Drive Style:
Torx
End Application:
F/a-18e/f
Thread Diameter:
Thread Diameter: 0.437 inches
0.437 inches
0.437 inches Grip Length:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi):
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name: Bolt, 100 degree tension head, gear drive recess
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name: Bolt, 100 degree tension head, gear drive recess Special Features:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name: Bolt, 100 degree tension head, gear drive recess Special Features: 125 ksi shear strength
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name: Bolt, 100 degree tension head, gear drive recess Special Features: 125 ksi shear strength Material:
0.437 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Agav Product Name: Bolt, 100 degree tension head, gear drive recess Special Features: 125 ksi shear strength Material: Nickel alloy 718

NSN 5305-01-526-4680

Close Tolerance Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0