NSN 5305-01-526-7962

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-526-7962 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.455 inches and 0.485 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3729 inches and 0.3813 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Point Style:** Flat **Internal Drive Style:** Torx **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear driverecess **Special Features:** 125 ksi shear strength Material: Nickel alloy 718 **Material Specification:** Aams 5662 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:**

Unjf

NSN 5305-01-526-7962

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0