

View Online at <https://aerobasegroup.com/nsn/5305-01-528-2705>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.190 inches

Fastener Length:

Between 0.300 inches and 0.347 inches

Head Style:

Flush

Head Diameter:

Between 0.363 inches and 0.394 inches

Head Height:

Between 0.237 inches and 0.284 inches

Hole Diameter:

Between 0.076 inches and 0.081 inches

Grip Diameter:

0.250 inches

Shank Unthreaded Hole Diameter:

0.076 inches locking feature and 0.081 inches locking feature

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 0.300 inches and 0.347 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.200 inches

Product Name:

Hi-torque bolt

Special Features:

One hundred degree flush reduced head

Material:

Steel

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.