## NSN 5305-01-528-5505

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-528-5505 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.795 inches **Fastener Length:** 0.875 inches **Head Style:** Flat countersunk **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Internal Drive Style:** Torx **End Application:** Mv-22 aircraft **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Screw, 100 degree flush head, full thread, 6 lobe recess **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5835 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Ams2700method 1, type2 assn standard all treatment responses or ams2700method, type8 class 1 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-528-5505

Machine Screw - Page 2 of 2



Fiig:

A500d0