NSN 5305-01-529-3696

Machine Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-529-3696
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.144 inches
Fastener Length:
1.250 inches
Head Style:
Flat countersunk
Spline Major Diameter:
Between 0.220 inches and 0.223 inches
Internal Drive Style:
Torx
End Application:
Mv-22 aircraft
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
5820 pounds per square inch
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Feat
Product Name:
Screw, 100 degree flush head, full thread, 6 lobe recess
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response or ams5835 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Ams2700method 1, type2 assn standard single treatment response or ams2700 method 1, type 8, cls 1 assn standard single treatment
response
Special Features:
Essential to weapon system performance or operation, or the preservation of life or safety of operating personnel
Thread Series Designator:
Unjf

N/a

Shelf Life:

NSN 5305-01-529-3696

Machine Screw - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A500d0