

View Online at <https://aerobasegroup.com/nsn/5305-01-529-7012>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.392 inches

**Fastener Length:**

1.145 inches

**Head Style:**

Hexagon

**Head Height:**

0.247 inches

**Width Between Flats:**

0.371 inches

**Spline Major Diameter:**

0.221 inches

**Locking Feature:**

Retainer

**Internal Drive Style:**

Torx

**End Application:**

F/a-22 raptor

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

4625 pounds per square inch

**Screw Material:**

Stainless steel

**Screw Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Bearing Surface Of Head Surface Treatment:**

Passivate

**Head Surface Treatment:**

Passivate

**Screw Surface Treatment:**

Passivate

**Shank Surface Treatment:**

Passivate

**Bearing Surface Of Head Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Head Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shank Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Special Features:**

Retainer ring slot each side

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0