NSN 5305-01-529-7012

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-529-7012

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.392 inches
Fastener Length:
1.145 inches
Head Style:
Hexagon
Head Height:
0.247 inches
Width Between Flats:
0.371 inches
Spline Major Diameter:
0.221 inches
Locking Feature:
Retainer
Internal Drive Style:
Torx
End Application:
F/a-22 raptor
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
4625 pounds per square inch
Screw Material:
Stainless steel
Screw Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Passivate
Head Surface Treatment:
Passivate
Screw Surface Treatment:
Passivate
Shank Surface Treatment:
Passivate
Bearing Surface Of Head Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-529-7012

Machine Screw - Page 2 of 2



Head Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shank Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Special Features:

Retainer ring slot each side

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0