## NSN 5305-01-529-7739

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-529-7739 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 1.763 inches and 1.793 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Grip Diameter:** Between 0.249 inches and 0.250 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 28 **Product Name:** Bolt, flat pan head Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Passivate or cadmium **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response or qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

**Unit Of Measure:** 

**Demilitarization:** 

No

N/a

## NSN 5305-01-529-7739

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0