NSN 5305-01-530-2406

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-530-2406

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.276 inches |
| Fastener Length: |
| Between 0.699 inches and 0.729 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Spline Major Diameter: |
| 0.155 inches |
| Grip Diameter: |
| Between 0.189 inches and 0.190 inches |
| Internal Drive Style: |
| Torx |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 0.438 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 3180 pounds per square inch |
| Material: |
| Stainless steel |
| Material Specification: |
| A286 assn standard single material response |
| Surface Treatment: |
| Passivate or cadmium |
| Surface Treatment Specification: |
| Ams-qq-p-35 federal specification single treatment response or ams-qq-p-46, type 2, class 2 federal specification single treatment |
| response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-01-530-2406

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

