## NSN 5305-01-530-2410

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-530-2410 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.511 inches and 0.541 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Spline Major Diameter:** 0.155 inches **Grip Diameter:** Between 0.189 inches and 0.190 inches **Internal Drive Style:** Torx **Thread Diameter:** 0.190 inches **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 3180 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Stainless steel **Material Specification:** A286 assn standard single material response **Surface Treatment:** Passivate or cadmium **Surface Treatment Specification:** Ams-qq-p-35 federal specification single treatment response or ams-qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-530-2410

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0