

View Online at <https://aerobasegroup.com/nsn/5305-01-530-2414>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

0.838 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Spline Major Diameter:

0.155 inches

Locking Feature:

Patch locking feature

Grip Diameter:

Between 0.188 inches and 0.189 inches

Point Diameter:

0.189 inches

Point Style:

Flat

Internal Drive Style:

Torx

Thread Diameter:

0.190 inches

Grip Length:

0.500 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

3180 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Screw, close tolerance.

Special Features:

End shall be flat and chamfered plus incomplete thread not to exceed two pitches.

Material:

Stainless steel

Material Specification:

A286 conforming to the chemistry of ams5731, ams5732, ams5737, or ams5853 assn standard single material response

Surface Treatment:

Cadmium or passivate

Surface Treatment Specification:

Ams-qq-p-35 or cadium plate per ams-qq-p-416, type ii, class 3. Assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0