NSN 5305-01-530-2414

Close Tolerance Screw - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5305-01-530-2414

Thread Direction:
Right-hand
Thread Length:
0.338 inches
Fastener Length:
0.838 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.376 inches and 0.385 inches
Spline Major Diameter:
0.155 inches
Locking Feature:
Patch locking feature
Grip Diameter:
Between 0.188 inches and 0.189 inches
Point Diameter:
0.189 inches
Point Style:
Flat
Internal Drive Style:
mioniai 2.176 ciylei
Torx
Torx
Torx Thread Diameter:
Torx Thread Diameter: 0.190 inches
Torx Thread Diameter: 0.190 inches Grip Length:
Torx Thread Diameter: 0.190 inches Grip Length: 0.500 inches
Torx Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi):
Torx Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle:
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name:
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw, close tolerance.
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw, close tolerance. Special Features:
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw, close tolerance. Special Features: End shall be flat and chamfered plus incomplete thread not to exceed two pitches.
Thread Diameter: 0.190 inches Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw, close tolerance. Special Features: End shall be flat and chamfered plus incomplete thread not to exceed two pitches. Material:

NSN 5305-01-530-2414

Close Tolerance Screw - Page 2 of 2



Surface	Treatment:

Cadmium or passivate

Surface Treatment Specification:

Ams-qq-p-35 or cadium plate per ams-qq-p-416, type ii, class 3. Assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0